



Robust industrial crane scale up to 10 t, with EC type approval [M]

**Features**

- With the TÜV certification mark, the scale meets the requirements of the standard EN 13155 (Non-fixed load lifting attachments/ Breakage resistance) and EN 61010-1 (Electrical safety)
- Professional device for robust applications in production, quality control, logistics etc. Because of its stable construction and robust design, it is ideal for continuous use in industrial environment
- High mobility:** thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations (production, warehouse, dispatch department etc.)

- Range of tare: 100 % of [Max]
- LED display with Gross/Tare/Net
- Standby function: display automatically switched off after 5 min without a change of load. Automatic activation with the touch of a key
- Tare:** Resets the display to „0“ when there is a load on the scale. Now removed or added loads are directly displayed
- Hook with safety catch,** non-revolving
- Infrared remote control** standard. Range up to 20 m. All functions can be selected. W×D×H 65×24×100 mm. Batteries included, 9 V

**Technical data**

- Superior display size:** digit height 25 mm, bright backlight for easy reading of weighing results, even in poor lighting conditions
- Rechargeable battery pack internal, operating time up to 150 h without backlight, charging time approx. 12 h
- Precision: 0,1% of [Max]
- Net weight  
HTS 1T-4AM: approx. 7 kg  
HTS 3T-3AM: approx. 9 kg  
HTS 6T-3AM: approx. 12 kg  
HTS 10T-3AM: approx. 20 kg
- Permissible ambient temperature -20 °C/40 °C

STANDARD						OPTION		FACTORY	
CAL EXT	ACCU	MULTI	DMS	1 DAY	3 YEARS WARRANTY	DAkkS	DAkkS	DAkkS	DAkkS
						+3 DAYS		+3 DAYS	

Model	Weighing range [Max] kg	Readout [d] = [e] g	Minimal load [Min] kg	3 Dimensions							Price excl. of VAT ex works €	Options			
				A	B	C	D	E	F	G		Verification		DAkkS Calibr. Certificate	
				mm	mm	mm	mm	mm	mm	mm			€		€
HTS 1T-4AM	1500	500	10	33	29	315	359	200	121	181	1190,-	950-130H	200,-	963-130H	165,-
HTS 3T-3AM	3000	1000	20	43	47	347	369	200	121	181	1250,-	950-132H	500,-	963-132H	500,-
HTS 6T-3AM	6000	2000	40	58	55	440	519	200	121	181	1320,-	950-132H	500,-	963-132H	500,-
HTS 10T-3AM	10000	5000	100	83	61	335	628	200	121	181	1460,-	950-133H	700,-	963-133H	700,-

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.