









## **Application examples**

- · retail shops
- · market places
- · farm shops
- · pick your own fruit and vegetable sales

**Note:** Official verification duty for commercial trade

## **Features**

- II KERN RPB-H: Elevated display backlit, revolving on column, height of stand approx.
   530 mm, must be ordered at purchase
- 2 Second display on the rear of the balance
- Three displays for weight display (verifiable), reference weight, total weight
- Unit price can be switched from €/kg to €/100 g
- · Memory (PLU) for 10 article prices
- Auto-clear-key: Unit price entry is automatically set to zero when scale is unloaded
- I High mobility: thanks to rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations

## Technical data

- · Large backlit LCD displays, digit height 20 mm
- Dimensions weighing surface, stainless steel, W×D 295×225 mm
- Overall dimensions W×D×H
   315×350×100 mm
- Net weight RPB: approx. 3,6 kg RPB-H: approx. 4,0 kg
- Permissible ambient temperature -10  $^{\circ}\text{C}/40~^{\circ}\text{C}$

## Accessories

- Protective working cover, standard, can be re-ordered, scope of delivery: 5 items, KERN CFS-A02S05, € 40,-
- Rechargeable battery pack internal, operating time up to 80 h without backlight, charging time approx. 14 h, KERN GAB-A04, € 40,-
- Tare pan made of stainless steel, ideal for weighing loose small parts, fruit, vegetables etc., W×D×H 370×240×20 mm, KERN RFS-A02, € 55,-
- Further details, plenty of further accessories and suitable printers see *Accessories*



OPTION	FACTO		
	DAkkS	M	
ACCU	+3 DAYS	+3 DA	

Model	Weighing range	Readout	Verification	Minimum load	Price	Options				
			value		excl. of VAT	Verification		DAkkS Calibr. Certificate		
10000000	[Max]	[d]	[e]	[Min]	ex works	MI		DKD		
KERN	kg	g	g	g	€	KERN	€	KERN	€	
Dual-range balance switches automatically to the next largest weighing range [Max] and readout [d].										
RPB 6K1DM	3   6	1   2	1   2	20	225,-	965-228	55,-	963-128	88,-	
RPB 15K2DM	6   15	2   5	2   5	40	225,-	965-228	55,-	963-128	88,-	
RPB 30K5DM	15   30	5   10	5   10	100	225,-	965-228	55,-	963-128	88,-	
with elevated display										
RPB 6K1DHM	3   6	1   2	1   2	20	250,-	965-228	55,-	963-128	88,-	
RPB 15K2DHM	6   15	2   5	2   5	40	250,-	965-228	55,-	963-128	88,-	
RPB 30K5DHM	15   30	5   10	5   10	100	250,-	965-228	55,-	963-128	88,-	

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible.

Verification at the factory, we need to know the full address of the location of use.